

Roll No.

Total Pages : 4

309404

May, 2019

B.Tech. (ME) IV SEMESTER

Advanced Strength of Materials (PCC-ME-208)

Time : 3 Hours]

[Max. Marks : 75

Instructions :

1. *It is compulsory to answer all the questions (1.5 marks each) of Part-A in short.*
2. *Answer any four questions from Part-B in detail.*
3. *Different sub-parts of a question are to be attempted adjacent to each other.*
4. *Assume suitable data if any missing.*

PART-A

1. (a) Differentiate between Zero, first and second order tensors. (1.5)
- (b) Which theories of failure give most conservative design? (1.5)
- (c) What is the importance of Hook's Law? (1.5)
- (d) What are the utility of Maxwell theorem? (1.5)
- (e) List the assumptions made to drive the expression for rotational stresses in rims and discs. (1.5)

309404/770/111/279

[P.T.O.
27/5

- (f) What is the difference between straight beam, beam with small initial curvature and beam with large curvature? (1.5)
- (g) Why trapezoidal section is preferred for crane hook design? (1.5)
- (h) Compare theories of failures graphical various. (1.5)
- (i) Differentiate sudden, gradual and Impact loading. (1.5)
- (j) Draw the graph for circumferential and radial stresses of a hollow cylinder. (1.5)

PART-B

2. A bolt is required to resist an axial tension of 25 kN and a transverse shear of 20 kN. Find the size of the bolt by
- The maximum principal stress theory.
 - The maximum shear stress theory.
 - The maximum distortion energy theory.
- The elastic limit of the material is 300 N/mm². Poisson's ratio = 0.3 and factor of safety = 3.0. (15)
3. (a) Drive an Expression for Castigliano's theorem. (5)
- (b) A bar 3 m long and 5cm diameter hangs vertically and has a collar securely attached to the lower end. Find the maximum stress inducted when,
- A weight of 2.5 kN falls from 12 cm on the collar.
 - A weight of 25 kN falls 1 cm on the collar
- Take $E = 2 \times 10^5$ N/mm². (10)

4. What is meant by a disc of uniform strength? Prove that the thickness of such a disc at any radius r is given by

$$t = t_0 \exp \left[\frac{-\rho \omega^2 r^2}{2\sigma} \right]$$

Where t_0 is the thickness at $r = 0$, σ is the stress due to rotation at ω radian/second. (15)

5. The horizontal cross-section of a crane hook is a trapezium with parallel sides 24 mm wide at the inside and 12 mm wide at the outside and the parallel sides are 30 mm apart. The hook carries a load of 6 kN, the line of load being at a horizontal distance of 300 mm from the inside edge of the horizontal cross-section through the center of curvature and the center of curvature being 36 mm from the same edge. Make calculation to determine the:
- location of neutral axis
 - maximum and minimum stresses induced in the hook. Show the variation of these stresses in the horizontal section. (15)
6. In a triaxial stress system, the six components of the stress at a point are given below:
- $$\sigma_x = 6 \text{ MN/m}^2 \quad \tau_{xy} = \tau_{yx} = 1 \text{ MN/m}^2$$
- $$\sigma_y = 5 \text{ MN/m}^2 \quad \tau_{yz} = \tau_{zy} = 3 \text{ MN/m}^2$$
- $$\sigma_z = 4 \text{ MN/m}^2 \quad \tau_{zx} = \tau_{xz} = 2 \text{ MN/m}^2$$
- Find the magnitude of three principal stresses. (15)

7. What is stress tensor? Drive an expression of small strain tensor and compatibility. (15)

